

solvoprint performance clear 80

Technical Information

➤ **General information**

- one-side self-adhesive, transparent, cadmium-free 80 µm polymeric PVC-film
- coated on one side with a solvent-free, age-resistant and permanently elastic acrylate adhesive
- glossy surface, printable with solvent based and UV-curable inks
- easy neutralising of adhesive
- no chemical reaction between solvent inks and acrylate adhesive

➤ **Areas of application**

- suitable as protection and printable film
- suitable for in- and outdoor applications
- outdoor durability (unprinted) up to 7 years – depending on application area and purpose
- universal protective film for a wide spectrum of analogue and digital printed images
- specially suitable for vehicle advertising

➤ **Processing & Handling**

- a sufficient drying (min. 24 hours) has to be ensured before application of protective films
- recommended print film: filmolux® performance print 80
- please refer to the general application tips in our current catalogue and on our homepage www.neschen.com

➤ **Advantages / Special Features**

- universal medium (wider printer- and ink spectrum)
- unproblematic adhesion on smooth and domed surfaces

solvoprint performance clear 80

Technical Information

➤ Technical Data

➤ Carrier:

Film type:	plasticized PVC-film, polymer, transparent, glossy		
Thickness [µm]:	75 ± 5	I approx. 3 mil	
Weight [g/m²]:	97 ± 5		
Breaking force [N/15mm]:	lengthwise:> 25	crosswise:> 25	DIN EN ISO 527-3, 50mm/min
Elongation at tear [%]:	lengthwise:> 230	crosswise:> 240	DIN EN ISO 527-3, 50mm/min
Tear resistance [N/mm²]:	lengthwise:> 20	crosswise:> 20	DIN EN ISO 527-3, 50mm/min

➤ Adhesive:

Adhesive Type:	waterbased polyacrylatic dispersion			
PH-value:	approx. 7.0			
Adhesive strength [N/25 mm]:	immediately: > 5.0	10 min: > 7.5	24h: > 15.0	AFERA 4001

➤ Backing:

Type:	double-sided PE laminated strong paper, neutral, one-sided siliconised		
Thickness [µm]:	163 ± 7	approx. 6.4 mil	
Weight [g/m²]:	145 ± 7		
Removal force [mN/cm]:	20-50	speed 300 mm/min	

➤ Others:

Handling/Storage conditions:	18° to 25°C / 60° to 80° F; 40 to 65% relative humidity		
Shelf life [Years]:	3		
Temperature stability:	-30°C to +60°C / -20° to +140° F	affixed to aluminium	

All tests were performed in accordance with 23/50-2, DIN 50014.